

MRD-BAS326H-484-HC

An electronic bar-tacking sewing machine with triple-size fully rotative hooks and upper and lower heat thread cutters. Operation for trimming thread ends remaining not stitched is unnecessary; so neat and highly productive sewing is possible.



Use



Seat belt



Sling belt

Mechanical properties

1. Equipped with triple-size fully rotative hooks to raise productivity (leading to longer bobbin replacement intervals)
2. Larger sewing area of 220 × 100 mm available for a wide variety of materials
3. Sturdy and reliable sewing even for extremely thick materials
4. The heat cutting system facilitates shortening thread ends remaining not cut from the stitches and in this way a “bird’s nest” can be avoided at the next sewing.
5. An automatic pin-insertion machine (no part number is given) is also available.

Specifications

| | | | |
|-----------------------------------|----------------------|------------------------------|---|
| Sewing area (X×Y) | 220 × 100/mm | Thread cutter | Separate (upper and lower) heat wires |
| Stitch type | 1-needle lockstitch | Data importing method | Internal memory, SD card,USB memory |
| Maximum sewing speed | 2,200 rpm | Sewing machine motor | AC servo motor 550 W |
| Stitch pitch | 0.05 to 12.7 mm | Power/consumption | Single-phase 100 V and three-phase 200 V/400 VA |
| Maximum number of stitches | 20,000 (per program) | Air pressure | 0.5 Mpa 1.81/min |
| | | Machine size | 1,080 × 1,000 × 1,350/mm |